

formatPro, v. 0.5: Format Profiles for mlRho

Bernhard Haubold

Max-Planck-Institute for Evolutionary Biology, Plön, Germany

October 29, 2012

1 Introduction

formatPro formats Profiles for analysis by mlRho. Take a look at the documentation for mlRho to see how formatPro is used.

2 Getting Started

formatPro was written in C on a computer running Linux and should work on any standard UNIX system. However, please contact me at haubold@evolbio.mpg.de if you have any problems with the program.

- Unpack the program

```
tar -xvzf formatPro_XXX.tgz
```

where XXX indicates the version.

- Change into the newly created directory

```
cd FormatPro_XXX
```

and list its contents

```
ls
```

- Generate formatPro

```
make
```

- List its options

```
./formatPro -h
```

3 Listing

The following listing documents the driver program for formatPro.

```
1  **** formatPro.c ****
* Description:
* Author: Bernhard Haubold, haubold@evolbio.mpg.de
* Date: Mon Oct 15 20:36:50 2012
****/
6 #include <stdio.h>
```

```

#include <stdlib.h>
#include <string.h>
#include <fcntl.h>
#include <unistd.h>
11 #include "interface.h"
#include "eprintf.h"
#include "profileTree.h"

void scanFile(FILE *fp, Args *args);

16 int main(int argc, char *argv[]) {
    int i, fd;
    char *version, *fileName;
    Args *args;
21    FILE *fp;
    Profile *profiles;
    Node *root;
    ContigDescr *cd;

26    version = "0.5";
    setprogname2("formatPro");
    args = getArgs(argc, argv);
    fileName = (char *)emalloc(256*sizeof(char));
    if(args->v)
        printSplash(version);
    if(args->h || args->e)
        printUsage(version);
    fileName = strcpy(fileName, args->n);
    fileName = strcat(fileName, ".pos");
36    fp = fopen(fileName, "wb");
    fwrite("pos", sizeof(char), 3, fp);
    root = NULL;
    profiles = NULL;
    cd = (ContigDescr *)emalloc(sizeof(ContigDescr));
    cd->n = 0;
    cd->len = NULL;
    if(args->numInputFiles == 0) {
        fd = 0;
        root = writePositions(fd, fp, root, cd, args);
41    }else{
        for(i=0;i<args->numInputFiles;i++){
            fd = open(args->inputFiles[i], O_RDONLY, 0);
            root = writePositions(fd, fp, root, cd, args);
            close(fd);
51        }
    }
    fclose(fp);
    profiles = getProfileArray();
    printf("#Positions_written_to_%s\n", fileName);
56    /* write profiles to file */
    writeProfiles(profiles, args);
    /* write contig lengths to file */
    cd = getContigDescr();
    writeContigs(cd, args);

```

```
61     freeProfileArray(profiles);
62     freeProfileTree(root);
63     free(args);
64     free(progname());
65     free(fileName);
66     return 0;
}
```

4 Change Log

- Version 0.1 (October 17, 2012)
 - First running version.
- Version 0.2 (October 18, 2012)
 - Switched from binary format to text format.
- Version 0.3 (October 18, 2012)
 - Mixture between text (profiles and contigs) and binary (positions).
 - Fixed bug in treatment of contig lengths from multiple files.
- Version 0.4 (October 20, 2012)
 - All files binary.
- Version 0.5 (October 29, 2012)
 - Included option for setting the minimum coverage (`-c`).