

# keywordMatcher, v. 1.20: Match a set of motifs against one or more sequences

Bernhard Haubold

Max-Planck-Institute for Evolutionary Biology, Plön, Germany

August 25, 2020

## 1 Introduction

The program `keywordMatcher` implements set matching based on the keyword tree data structure as described by ?. The program takes as input one or more patterns and one or more sequences in FASTA format. Its output are the match positions of the patterns.

## 2 Getting Started

`keywordMatcher` was written in C on a computer running Linux and should work on any standard UNIX system. However, please contact me at `haubold@evolbio.mpg.de` if you have any problems with the program.

- Unpack the program

```
tar -xvzf keywordMatcher_XXX.tgz
```

where XXX indicates the version.

- Change into the newly created directory

```
cd KeywordMatcher_XXX
```

and list its contents

```
ls
```

- Generate `keywordMatcher`

```
make
```

- List its options

```
./keywordMatcher -h
```

- Run program with two patterns entered on the command line

```
./keywordMatcher -p 'CCGGGC|GCGGCG' mgGenome.fasta
```

- Include reverse strand

```
./keywordMatcher -r -p 'CCGGGC|GCGGCG' mgGenome.fasta
```

- Run program with a set of patterns passed as a FASTA-file

```
keywordMatcher -r -f patterns.fasta mgGenome.fasta
```

- Visualize a keyword tree:

```
keywordMatcher -t kt.tex -p 'ACA|AC|ACG|GCG' ../Data/test.fasta > /dev/null
```

This generates the L<sup>A</sup>T<sub>E</sub>X file kt.tex containing the keyword tree for the keywords ACA, AC, ACG, GCG. To view it, either include kt.tex in your L<sup>A</sup>T<sub>E</sub>X document, or typeset the wrapper file ktWrapper.tex, which was also generated.

### 3 Listing

The following listing documents the driver program for keywordMatcher.

```
1  **** keywordMatcher.c ****
 * Description: Match a set of patterns against a text using a
 *   keyword tree.
 * Reference: Gusfield, D. (1997). Algorithms on Strings, Trees,
 *   and sequences; Computer Science and Computational Biology.
6   *   CUP, p. 52ff.
 * Author: Bernhard Haubold, haubold@evolbio.mpg.de
 * File created on Fri Aug 27 19:30:32 2004.
 ****
#include <stdio.h>
11 #include <stdlib.h>
#include <string.h>
#include <ctype.h>
#include <time.h>
#include <assert.h>
16 #include "eprintf.h"
#include "StringUtil.h"
#include "keywordMatcher.h"
#include "ktree.h"
#include "construct.h"
21 #include "drawTree.h"

char *getWrapperFileName(char *fileName) {
    char *buffer;
    int i;
26
    buffer = (char *)emalloc(1024 * sizeof(char));
    i = 0;
    while(fileName[i] != '.' && fileName[i] != '\0') {
        buffer[i] = fileName[i];
        i++;
    }
    buffer[i] = '\0';
    strcat(buffer, "Wrapper.tex");
    return buffer;
31 }

char *getDvipsFileName(char *fileName) {
    char *buffer;
```

```

int i;
41
buffer = (char *)emalloc(1024 * sizeof(char));
i = 0;
while(fileName[i] != '.' && fileName[i] != '\0'){
    buffer[i] = fileName[i];
46    i++;
}
buffer[i] = '\0';
strcat(buffer, ".dvi");
return buffer;
51 }

char *getPsFileName(char *fileName) {
    char *buffer;
    int i;
56
buffer = (char *)emalloc(1024 * sizeof(char));
i = 0;
while(fileName[i] != '.' && fileName[i] != '\0'){
    buffer[i] = fileName[i];
61    i++;
}
buffer[i] = '\0';
strcat(buffer, ".ps");
return buffer;
66 }

int main(int argc, char *argv[]){
    int i;
    Args *args;           /* arguments */
71    char *version;        /* program version */
    FILE *fp;
    KTree *ktree;
    char *wrapperFile, *dvipsFile, *psFile;

    version = "1.20";
    setprogname2("keywordMatcher");
    args = getArgs(argc, argv);
    if(args->v)
        printSplash(version);
81    if(args->h || args->e)
        printUsage(version);
    ktree = getKeywordTree(args);
    if(args->t) {
        wrapperFile = getWrapperFileName(args->t);
        dvipsFile = getDvipsFileName(wrapperFile);
86        psFile = getPsFileName(wrapperFile);
        fp = efopen(wrapperFile, "w");
        printLatexHeader(fp);
        fprintf(fp, "\\begin{center}\\n\\input{%s}\\n\\end{center}\\n\\end{document
            }", args->t);
91        fclose(fp);
        fp = efopen(args->t, "w");
}

```

```

drawTree(fp, ktree->root);
fclose(fp);
fprintf(stderr, "#_The_keyword_tree_is_contained_in_%s;_to_view_it,_
either_include_it_in_your_document,\n", args->t);
96 fprintf(stderr, "#_or_run_latex_%s;_dvips_%s_to_generate_%s\n",
wrapperFile,dvipsFile,psFile);
fprintf(stderr, "#_To_print_output-set instead_of_node_labels:_adjust_
commenting_at_end_of_%s\n", args->t);
}
101 if(args->numInputFiles == 0) {
    fp = stdin;
    searchSingleSeq(fp, args, ktree);
}else{
    for(i=0; i<args->numInputFiles; i++) {
        fp = efopen(args->inputFiles[i], "r");
        searchMultipleSeq(fp, args, ktree);
        fclose(fp);
106    }
}
free(args);
free(progname());
111 return 0;
}

```

## 4 Change Log

- Version 1.13 (March 31st, 2016)
  - Cleaned up compiler warnings
  - Changed email address from fh-weihenstephan to evolbio.mpg
  - Included genome of *Mycoplasma genitalium* in distribution (`mgGenome.fasta`)
- Version 1.14 (April 15, 2017)
  - Brought interface in line with standard UNIX behavior; in particular, abolished the `-t` option.
  - Included this documentation.
- Version 1.15 (June 7, 2017)
  - Replaced `construct.initializeTree()` by `construct.getNode()`.
  - Added code for drawing keyword tree in  $\text{\LaTeX}$ .
- Version 1.16 (June 9, 2017)
  - Now generates  $\text{\LaTeX}$  wrapper whenever the keyword tree is written to  $\text{\LaTeX}$ .
- Version 1.17 (June 9, 2017)
  - Improved interface to prevent run on null pattern.
  - Improved sizing of the pspicture.
- Version 1.18 (November 14, 2017)
  - $\text{\LaTeX}$ -output now includes output set. This needs to be activated by uncommenting the corresponding lines at the end of the included file.

- Improved placement of the pspicture.
- Version 1.19 (December 15, 2018)
  - Fixed bug in getArgs in interface.c.
- Version 1.20 (August 25, 2020)
  - Fixed bug in reading of patterns from argv or file. In both cases one byte too little was allocated.